



**EM Retailer EAS System** 

- Superior and patented 3D EM detection
- Detection of labels placed on metallic items and inside of aluminium bags
- Digital signal processing





Retailor-N	Retailor Mono  1 x master antenna 1 x AC/DC adaptor
Retailor-NN	Retailor single Mono aisle system 2 x master antennas 2 x AC/DC adaptors and cable set
Retailor-NNN	Retailor dual Mono aisle system 3 x master antennas 3 x AC/DC adaptors and cable set
Retailor-MS	Retailor single aisle system  1 x master antenna 1 x slave antenna 1 x SWS power supply with cable set
Retailor-MM	Retailor single aisle system  1 x master antenna 1 x SWS power supply with cable set
Retailor-MSSJ	Retailor dual aisle system  1 x master antenna 2 x slave antennas 1 x JWS power supply unit with cable set
Retailor-MSS	Retailor dual aisle system  1 x master antenna 2 x slave antennas 1 x SWS power supply unit with cable set
Retailor-MMS	Retailor dual aisle system  2 x master antennas  1 x slave antenna  2 x SWS power supply units with cable sets
Retailor-MMM	Retailor dual aisle system 3 x master antennas 2 x SWS power supply units with cable sets

Dimensions	modifiable standard height: 157 cm width: 64 cm thickness of antenna frame: 2.5 cm base thickness: 9 cm
Voltage	100V - 240 Vac; 50/60Hz; Grounded
POWER CONSUMPTION	max. 500VA
TX FREQUENCY	ca. 200 Hz
OPERATION TEMPERATURE	+10°C - +50°C
WEIGHT	master antenna: 18,5 kg slave antenna: 18 kg power supply: 6 kg
TYPICAL DETECTION RANGE	90 cm - 110 cm 35.4 inch - 44 inch
ALARM Alarm Interface board	<ul> <li>Visual/Audio signal</li> <li>optional (NO/NC Relay output)</li> <li>programmable sound and light alarm</li> <li>sequences</li> </ul>



## **Contact Information**

Tel Number: 021 572 5321

Fax Number: 021 572 5348

Office Cell: 082 974 3605

Technical Assistance:(24/7)

0861 182 448

www.tagtron.net